



OECD approval number

2/2 190

Restricted Code

OECD approval date

25/10/2004

Make

Case IH

Model

MX 285

Type

4 WD


MFWD

Manufacturer

CNH America LLC

Testing station:

Nebraska Tractor Test Laboratory, Lincoln, USA



Engine, Transmission, Power take-off Specifications

<i>Make, Model</i>	Consolidated Diesel	6TAA-8304
<i>Type, Supercharging</i>	Direct injection	Yes
<i>Cylinders, Disposition</i>	6	vertical in line
<i>Capacity, Cooling</i>	8268 cm ³	Liquid
<i>Gear box</i>		Mechanical powershift
<i>Number of forward and reverse speeds</i>	18	4
<i>Speed at rated engine speed</i>	from 3.15	to 36.39 km/h
<u>Standard Power take-off speed</u>	<u>540 min⁻¹</u>	<u>1000 min⁻¹</u>
<i>Power take-off speed at rated engine speed</i>		1003 min ⁻¹
<i>Diameter of the shaft</i>		44 mm
<i>Number of splines</i>		20

Power take-off TestTwo hours test at maximum power

<i>Power, Engine and Power take-off speed</i>	205.9 kW	1700 min ⁻¹	853 min ⁻¹
<i>Hourly and specific consumption</i>		55.75 l/h	228 g/kWh

Test at maximum power at rated engine speed

<i>Power, Engine and Power take-off speed</i>	180.6 kW	2000 min ⁻¹	1003 min ⁻¹
<i>Hourly and specific consumption</i>		51.50 l/h	240 g/kWh

Test at standard Power take-off speed

<i>Power, Engine and Power take-off speed</i>	180.6 kW	2000 min ⁻¹	1003 min ⁻¹
<i>Hourly and specific consumption</i>		51.50 l/h	240 g/kWh

Torque rise

48.7 %

Maximum torque, Engine speed corresponding1283.0 Nm 1402 min⁻¹**Drawbar Test***Front tyres, Rear tyres*

420/90 R 30 520/85 R 42

Test with tractorunballasted ballasted*Total Mass*

9815 kg 14213 kg

Maximum drawbar pull

92.6 kN 133.7 kN

at speed of

5.07 km/h 3.70 km/h

Maximum power

175.0 kW 176.7 kW

at speed of

8.86 km/h 6.75 km/h

Hydraulic Performance and Power Lift Test*Hydraulic system*

Closed centre

At maximum hydraulic power*Flow rate, Pressure, Power (couplers: 1 pair)**Flow rate, Pressure, Power (couplers: 2 pairs or +)* 145.7 l/min 19.6 MPa 47.7 kWMaximum lifting force*at the hitch points, at frame (Cat. 3, 2xØ 95 mm cylinders)* 85.0 kN 72.8 kN*at the hitch points, at frame (Cat. 3, Euro, 1xØ 95 & 1xØ 105 mm cyl.)* 79.6 kN 74.3 kN*at the hitch points, at frame (Cat. 3, 1xØ 95 & 1xØ 105 mm cyl.)* 96.7 kN 79.8 kN