



OECD approval number
OECD approval date
Make
Model
Type

2/2 414
26/06/2008
Challenger
MT 565B
4 WD


Manufacturer
Testing station:

F44E23GH113K - 40 km/h
AGCO S.A.
Cemagref, Antony, France

Challenger MT 565B

4 RM/WD

OCDE/OECD 2/2414



Engine, Transmission, Power take-off Specifications

<i>Make, Model</i>	Perkins/Caterpillar	T3294/2200
<i>Type, Supercharging</i>	Direct injection	Yes
<i>Cylinders, Disposition</i>	6	vertical in line
<i>Capacity, Cooling</i>	6600 cm ³	Liquid
<i>Gear box</i>		Mechanical
<i>Number of forward and reverse speeds</i>	24	24
<i>Speed at rated engine speed</i>	from 1.72	to 40.48 km/h
<i>Standard Power take-off speed</i>	540 min ⁻¹	1000 min ⁻¹
<i>Power take-off speed at rated engine speed</i>	594 min ⁻¹	1100 min ⁻¹
<i>Diameter of the shaft</i>	34.9 mm	34.9 mm
<i>Number of splines</i>	6	21

Power take-off TestTwo hours test at maximum power

<i>Power, Engine and Power take-off speed</i>	138.6 kW	1800 min ⁻¹	900 min ⁻¹
<i>Hourly and specific consumption</i>		40.62 l/h	250 g/kWh

Test at maximum power at rated engine speed

<i>Power, Engine and Power take-off speed</i>	121.3 kW	2200 min ⁻¹	1100 min ⁻¹
<i>Hourly and specific consumption</i>		38.41 l/h	270 g/kWh

Test at standard Power take-off speed

<i>Power, Engine and Power take-off speed</i>	132.2 kW	2000 min ⁻¹	1000 min ⁻¹
<i>Hourly and specific consumption</i>		40.62 l/h	262 g/kWh

Torque rise

<i>Maximum torque, Engine speed corresponding</i>	815.4 Nm	1199 min ⁻¹	54.9 %
---	----------	------------------------	--------

Drawbar Test

<i>Front tyres, Rear tyres</i>	16.9 R 30	520/85 R 42
<i>Test with tractor</i>	<u>unballasted</u>	<u>ballasted</u>
<i>Total Mass</i>	7545 kg	9975 kg
<i>Maximum drawbar pull</i>	67.6 kN	88.6 kN
<i>at speed of</i>	2.14 km/h	1.81 km/h
<i>Maximum power</i>	124.2 kW	122.8 kW
<i>at speed of</i>	10.15 km/h	7.12 km/h

Hydraulic Performance and Power Lift Test

<i>Hydraulic system</i>	Closed centre		
<i>At maximum hydraulic power</i>			
<i>Flow rate, Pressure, Power (couplers: 1 pair)</i>	89.8 l/min	14.1 MPa	21.1 kW
<i>Flow rate, Pressure, Power (couplers: 2 pairs or +)</i>	104.2 l/min	15.3 MPa	26.6 kW
<i>Maximum lifting force</i>			
<i>at the hitch points, at frame</i>	70.0 kN	62.7 kN	

