



OECD approval number
OECD approval date
Make
Model
Type


2/2 510
07/09/2009
Case IH
Farmall 95
4 WD

JPBS4A - JX95 - 12 speeds - 30 km/h

Manufacturer: Türk Traktör ve Ziraat Makinaları A.Ş.
Testing station: TAMTEST, Ankara, Turkey

Case IH Farmall 95
4 RM/WD

OCDE/OECD 2/2510



Engine, Transmission, Power take-off Specifications

<i>Make, Model</i>	Iveco, FPT	445TA/MNE
<i>Type, Supercharging</i>	Direct injection	Yes
<i>Cylinders, Disposition</i>	4	vertical in line
<i>Capacity, Cooling</i>	4485 cm ³	Liquid
<i>Gear box</i>		Mechanical synchronized
<i>Number of forward and reverse speeds</i>	12	12
<i>Speed at rated engine speed</i>	from 1.82	to 29.98 km/h
<i>Standard Power take-off speed</i>	540 min ⁻¹	1000 min ⁻¹
<i>Power take-off speed at rated engine speed</i>	614 min ⁻¹	1050 min ⁻¹
<i>Diameter of the shaft</i>	35 mm	35 mm
<i>Number of splines</i>	6	21

Power take-off TestTwo hours test at maximum power

<i>Power, Engine and Power take-off speed</i>	60.2 kW	2500 min ⁻¹	1050 min ⁻¹
<i>Hourly and specific consumption</i>		19.94 l/h	276 g/kWh

Test at maximum power at rated engine speed

<i>Power, Engine and Power take-off speed</i>	60.2 kW	2500 min ⁻¹	1050 min ⁻¹
<i>Hourly and specific consumption</i>		19.94 l/h	276 g/kWh

Test at standard Power take-off speed

<i>Power, Engine and Power take-off speed</i>	60.1 kW	2381 min ⁻¹	1000 min ⁻¹
<i>Hourly and specific consumption</i>		19.52 l/h	270 g/kWh

Torque rise

<i>Maximum torque, Engine speed corresponding</i>	378.8 Nm	1050 min ⁻¹	64.7 %
---	----------	------------------------	--------

Drawbar Test

<i>Front tyres, Rear tyres</i>	13.6 R 24	18.4 R 34
<i>Test with tractor</i>	<u>unballasted</u>	<u>ballasted</u>
<i>Total Mass</i>	3654 kg	
<i>Maximum drawbar pull</i>	33.0 kN	Not
<i>at speed of</i>	5.36 km/h	required
<i>Maximum power</i>	55.5 kW	
<i>at speed of</i>	9.49 km/h	

Hydraulic Performance and Power Lift Test

<i>Hydraulic system</i>			Opened centre
<i>At maximum hydraulic power</i>			
<i>Flow rate, Pressure, Power (couplers: 1 pair)</i>	55.6 l/min	12.5 MPa	11.6 kW
<i>Flow rate, Pressure, Power (couplers: 2 pairs or +)</i>	55.6 l/min	12.5 MPa	11.6 kW
<i>Maximum lifting force</i>			
<i>at the hitch points, at frame</i>		21.4 kN	16.9 kN

