



OECD approval number

2/2 516

OECD approval date

29/10/2009

Make

Massey Ferguson

Model

5455

Type

4 WD

D24D22GF613A - 40 km/h

Manufacturer:

AGCO S.A.


Testing station:

Cemagref, Antony, France

Massey Ferguson 5455

4 RM/WD

OCDE/OECD 2/2516



Engine, Transmission, Power take-off Specifications

<i>Make, Model</i>	Perkins	1104D-E44TA (3263/2200)
<i>Type, Supercharging</i>	Direct injection	Yes
<i>Cylinders, Disposition</i>	4	vertical in line
<i>Capacity, Cooling</i>	4400 cm ³	Liquid
<i>Gear box</i>		Mechanical
<i>Number of forward and reverse speeds</i>	16	16
<i>Speed at rated engine speed</i>	from 2.12	to 40.21 km/h
<i>Standard Power take-off speed</i>	540 min ⁻¹	1000 min ⁻¹
<i>Power take-off speed at rated engine speed</i>	601 min ⁻¹	1100 min ⁻¹
<i>Diameter of the shaft</i>	34.9 mm	34.9 mm
<i>Number of splines</i>	6	21

Power take-off TestTwo hours test at maximum power

<i>Power, Engine and Power take-off speed</i>	81.5 kW	2000 min ⁻¹	1000 min ⁻¹
<i>Hourly and specific consumption</i>		24.46 l/h	256 g/kWh

Test at maximum power at rated engine speed

<i>Power, Engine and Power take-off speed</i>	69.2 kW	2199 min ⁻¹	1100 min ⁻¹
<i>Hourly and specific consumption</i>		22.71 l/h	280 g/kWh

Test at standard Power take-off speed

<i>Power, Engine and Power take-off speed</i>	81.5 kW	2000 min ⁻¹	1000 min ⁻¹
<i>Hourly and specific consumption</i>		24.46 l/h	256 g/kWh

Torque rise

<i>Maximum torque, Engine speed corresponding</i>	482.3 Nm	1401 min ⁻¹	60.4 %
---	----------	------------------------	--------

Drawbar Test*Front tyres, Rear tyres*

<i>Test with tractor</i>	14.9 R 28	18.4 R 38
--------------------------	-----------	-----------

*Total Mass**Maximum drawbar pull**at speed of**Maximum power**at speed of*

<u>unballasted</u>	<u>ballasted</u>
4410 kg	
41.6 kN	Not
2.29 km/h	required
69.0 kW	
9.09 km/h	

Hydraulic Performance and Power Lift Test*Hydraulic system*

Opened centre

At maximum hydraulic power*Flow rate, Pressure, Power (couplers: 1 pair)**Flow rate, Pressure, Power (couplers: 2 pairs or +)*Maximum lifting force*at the hitch points, at frame*

41.5 kN	34.0 kN
---------	---------

