



OECD approval number
OECD approval date
Make
Model
Type


Manufacturer:
Testing station:

2/2 631
07/09/2011
Case IH
JX70
2WD

Mechanical, - 30 km/h
Türk Traktör ve Ziraat Mak.A.Ş.
TAMTEST, Ankara, Turkey

Case IH JX70
2 RM/WD

OCDE/OECD 2/2 631



Engine, Transmission, Power take-off Specifications

<i>Make, Model</i>	TTF	8035.25C.313T
<i>Type, Supercharging</i>	diesel engine	Yes
<i>Cylinders, Disposition</i>	3	vertical in line
<i>Capacity, Cooling</i>	2930 cm ³	Liquid
<i>Gear box</i>		Mechanical
<i>Number of forward and reverse speeds</i>	12	12
<i>Speed at rated engine speed</i>	from 1,77	to 29,27 km/h
<u>Standard Power take-off speed</u>	540 min ⁻¹	1000 min ⁻¹
<i>Power take-off speed at rated engine speed</i>	565 min ⁻¹	
<i>Diameter of the shaft</i>	35 mm	Not
<i>Number of splines</i>	6	Applicable

Power take-off TestOne hour test at maximum power

<i>Power, Engine and Power take-off speed</i>	43,2 kW	2100 min ⁻¹	516 min ⁻¹
<i>Hourly and specific consumption</i>		14,41 l/h	279 g/kWh

Test at maximum power at rated engine speed

<i>Power, Engine and Power take-off speed</i>	42,1 kW	2300 min ⁻¹	565 min ⁻¹
<i>Hourly and specific consumption</i>		15,01 l/h	298 g/kWh

Test at standard Power take-off speed

<i>Power, Engine and Power take-off speed</i>	42,8 kW	2198 min ⁻¹	540 min ⁻¹
<i>Hourly and specific consumption</i>		14,71 l/h	287 g/kWh

Torque rise

<u>Maximum torque, Engine speed corresponding</u>	242,6 Nm	1000 min ⁻¹
---	----------	------------------------

Drawbar Test

<i>Front tyres, Rear tyres</i>	7.50-16	380/85R30
<u>Test with tractor</u>	unballasted	ballasted
<i>Total Mass</i>	3044 kg	
<i>Maximum drawbar pull</i>	18.16 kN	
<i>at speed of</i>	5,18 km/h	Not
<i>Maximum power</i>	35,8 kW	Applicable
<i>at speed of</i>	12,2 km/h	

Hydraulic Performance and Power Lift Test

<i>Hydraulic system</i>			Open center
<u>At maximum hydraulic power</u>			
<i>Flow rate, Pressure, Power (couplers: 1 pair)</i>	27,7 l/min	16,5 MPa	7,6 kW
<i>Flow rate, Pressure, Power (couplers: 2 pairs or +)</i>	27,7 l/min	16,5 MPa	7,6 kW
<u>Maximum lifting force</u>			
<i>at the hitch points, at frame</i>		22,8 kN	17,9 kN