




OECD approval number
OECD approval date
Make
Model
Type

Manufacturer:
Testing station:

2/2 793
08/11/2013
MASSEY FERGUSON
6614
4WD
Dyna VT - 40 km/h
AGCO S.A.
IRSTEA – France

MASSEY FERGUSON 6614
4 RM/WD

OCDE/OECD 2/2 793



Engine, Transmission, Power take-off Specifications

<i>Make, Model</i>	AGCO POWER	49 AWI 898
<i>Type, Supercharging</i>	Direct injection	Yes
<i>Cylinders, Disposition</i>	4	vertical in line
<i>Capacity, Cooling</i>	4910 cm ³	Liquid
<i>Gear box</i>		Dyna VT
<i>Number of forward and reverse speeds</i>	-	-
<i>Speed at rated engine speed</i>	from 0	to 40,00 km/h
<u>Standard Power take-off speed</u>	540 min ⁻¹	1000 min ⁻¹
<i>Power take-off speed at rated engine speed</i>	576 min ⁻¹	1084 min ⁻¹
<i>Diameter of the shaft</i>	34,9 mm	34,9 mm
<i>Number of splines</i>	6	21

Power take-off TestOne hour test at maximum power

<i>Power, Engine and Power take-off speed</i>	91,7 kW	2002 min ⁻¹	983 min ⁻¹
<i>Hourly and specific consumption</i>		26,79 l/h	244 g/kWh

Test at maximum power at rated engine speed

<i>Power, Engine and Power take-off speed</i>	82,0 kW	2198 min ⁻¹	1079 min ⁻¹
<i>Hourly and specific consumption</i>		25,70 l/h	262 g/kWh

Test at standard Power take-off speed

<i>Power, Engine and Power take-off speed</i>	88,7 kW	2035 min ⁻¹	1000 min ⁻¹
<i>Hourly and specific consumption</i>		26,41 l/h	249 g/kWh

Torque rise

<u>Maximum torque, Engine speed corresponding</u>	555,1 Nm	1298 min ⁻¹
---	----------	------------------------

Drawbar Test

<i>Front tyres, Rear tyres</i>	480/70 R28	580/70 R38
<u>Test with tractor</u>	<u>unballasted</u>	<u>ballasted</u>
<i>Total Mass</i>	7150 kg	
<i>Maximum drawbar pull</i>	61,0 kN	
<i>at speed of</i>	3,56 km/h	Not
<i>Maximum power</i>	72,0 kW	Applicable
<i>at speed of</i>	7,67 km/h	

Hydraulic Performance and Power Lift Test

<i>Hydraulic system</i>			Closed centre
<u>At maximum hydraulic power</u>			
<i>Flow rate, Pressure, Power (couplers: 1 pair)</i>	106,2 l/min	13,3 MPa	23,6 kW
<i>Flow rate, Pressure, Power (couplers: 2 pairs or +)</i>	110,2 l/min	16,0 MPa	29,4 kW
<u>Maximum lifting force</u>			
<i>at the hitch points, at frame</i>		57,5 kN	52,3 kN