




OECD approval number
OECD approval date
Make
Model
Type

Manufacturer:
Testing station:

2/2 840
14/05/2014
NEW HOLLAND
T 4.115
4WD
Mechanical - 40 km/h
CNH Industrial Europe Holding S.A.
DISTAL – Italy

NEW HOLLAND T 4.115
4WD

OCDE/OECD 2/2 840



Engine, Transmission, Power take-off Specifications

<i>Make, Model</i>	FTP Industrial	F5DFL413H
<i>Type, Supercharging</i>	Direct injection	Yes
<i>Cylinders, Disposition</i>	4	vertical in line
<i>Capacity, Cooling</i>	3387 cm ³	Liquid
<i>Gear box</i>		Mechanical
<i>Number of forward and reverse speeds</i>	12	12
<i>Speed at rated engine speed</i>	from 2,15	to 38,22 km/h
<u>Standard Power take-off speed</u>	540 min ⁻¹	1000 min ⁻¹
<i>Power take-off speed at rated engine speed</i>	565 min ⁻¹	1017 min ⁻¹
<i>Diameter of the shaft</i>	35 mm	35 mm
<i>Number of splines</i>	6	21

Power take-off TestOne hour test at maximum power

<i>Power, Engine and Power take-off speed</i>	77,3 kW	1901 min ⁻¹	467 min ⁻¹
<i>Hourly and specific consumption</i>		22,20 l/h	241 g/kWh

Test at maximum power at rated engine speed

<i>Power, Engine and Power take-off speed</i>	73,6 kW	2300 min ⁻¹	565 min ⁻¹
<i>Hourly and specific consumption</i>		23,53 l/h	268 g/kWh

Test at standard Power take-off speed

<i>Power, Engine and Power take-off speed</i>	74,9 kW	2198 min ⁻¹	540 min ⁻¹
<i>Hourly and specific consumption</i>		22,98 l/h	257 g/kWh

Torque rise

<i>Maximum torque, Engine speed corresponding</i>	436,9 Nm	1502 min ⁻¹
---	----------	------------------------

Drawbar Test

<i>Front tyres, Rear tyres</i>	440/65 R24	540/65 R34
<u>Test with tractor</u>	<u>unballasted</u>	<u>ballasted</u>
<i>Total Mass</i>	3800 kg	
<i>Maximum drawbar pull</i>	30,65 kN	
<i>at speed of</i>	4,39 km/h	Not
<i>Maximum power</i>	59,48 kW	Applicable
<i>at speed of</i>	9,10 km/h	

Hydraulic Performance and Power Lift Test

<i>Hydraulic system</i>		Open centre
<u>At maximum hydraulic power</u>		
<i>Flow rate, Pressure, Power (couplers: 1 pair)</i>	40,36 l/min	17,83 MPa 12,00 kW
<i>Flow rate, Pressure, Power (couplers: 2 pairs or +)</i>		Not Applicable
<u>Maximum lifting force</u>		
<i>at the hitch points, at frame</i>	24,1 kN	17,3 kN