OECD ABSTRACT OF AGRICULTURAL AND FORESTRY TRACTOR PERFORMANCE TEST

OECD Approval Number	2/2 940
OECD Approval Date	15/03/2016
Make	FERRARI
Model	COBRAM 60 RS
Make	BCS
Model	VALIANT 600 RS
Make	PASQUALI
Model	EOS 6.60
Туре	4 WD
Transmission	mechanical
Speed	30 km/h
Manufacturer	BCS S.p.A.
Testing Station	DISTAL – Italy







[Page 1/5]

SPECIFICATIONS

ENGINE

Capacity2482 cm³CoolingLiquid	Make Model Type Supercharging Cylinders Disposition Capacity Cooling	
-------------------------------	---	--

TRANSMISSION

Gear box		Mechanical
Number of forward and reverse speeds	12	12
Speed at rated engine speed	from 0,82	to 32,6 km/h

POWER TAKE-OFF SPECIFICATIONS

Standard Power take-off speed	<u>540 min⁻¹</u>	<u>1000 min⁻¹</u>
Power take-off speed at rated engine speed	585 min ⁻¹	
Diameter of the shaft	35 mm	Not
Number of splines	6	Available





2/2 940

PTO TEST RESULTS

<u>One hour test at maximum power</u>			
Power, Engine and Power take-off speed	32,2 kW	2600 min ⁻¹	584 min ⁻¹
Hourly and specific consumption	- ,	10,81 l/h	280 g/kWh
Hourly and specific urea consumption		-	-
Test at maximum power at rated engine speed			
Power, Engine and Power take-off speed	32,2 kW	2600 min ⁻¹	584 min ⁻¹
Hourly and specific consumption		10,81 l/h	280 g/kWh
Hourly and specific urea consumption			
Test at standard Power take-off speed			
Power, Engine and Power take-off speed	31,6 kW	2403 min ⁻¹	540 min ⁻¹
Hourly and specific consumption	- ,-	10,31 l/h	273 g/kWh
Hourly and specific urea consumption			
<u>Torque rise</u>			30,0 %
Maximum torque, Engine speed corresponding		153,9 Nm	1491 min ⁻¹
40			
35			
30			
25 20 20 15 20 10 5 5 5	•)	210 2	
20		180 0	
		150 0	
	•		
	•	120 0	
		90 Z	
Q 0	•	60	
		30	
		0	
12		500	
5 "		475	
si ¹⁰		450 005	
8 9	•)	425 5	
	- 1	400 _	
Ŷ 7		375 0	
Q 6		350	
		325 00	
٩ ٩			
2			
	-		
2 1400 1600 1800 2000	2200 2400 26	250 00 2800	
Vitesse de rotation du mot	eur / Engine speed	rev/min	
			STE STOR





[Page 3/5]

open centre 20,5 ± 0,5 MPa

FERRARI BCS PASQUALI

PARTICULATE FILTER ACTIVE REGENERATION FUEL USE

Not Applicable

HYDRAULIC PERFORMANCE AND POWER LIFT TEST

Hydraulic system	
Relief valve pressure setting (tolerance):	

HYDRAULIC PERFORMANCES

<u>At maximum hydraulic power</u>			
Flow rate, Pressure, Power (couplers: 1 pair)	22,57 l/min	15,6 MPa	5,87 kW
Flow rate, Pressure, Power (couplers: 2 pairs or +)		Not	Applicable

POWER LIFT

Maximum lifting force at the hitch points at the frame


8,52 kN 5,24 kN







DRAWBAR TEST



Not available



